



VERSA-GRIP™ 102

VG-102

Indoor/Outdoor Water Based Duct Sealant

A versatile, **all purpose duct sealant** for use on all types of metal duct, glass fiber duct board, and flex duct, as well as duct fabric and flexible tubing runouts. VERSA-GRIP incorporates a built-in **fiber reinforcement** for **exceptional strength**, with UV inhibitors for **extended outdoor exposure**.

TECHNICAL DATA

Color	White
Consistency	Heavy textured
Base	Synthetic latex
Solvent	Water
Weight per Gallon	10.4 lbs. (+/- .2)
Solids Content	64% (+/- 2)
Viscosity	Thixotropic
Coverage (per gal.)	Up to 320 lin. ft. 3" width, 20 mil thickness
Shore A Hardness	>20
Flexibility	Passes 1/4 inch mandrel bend
Time to Test	48 hours*
Service Temperature	-20°F to 200°F
Surface Burning	Flame Spread 5, Smoke developed 0, (When tested in accordance with ASTM E84)
Weather Resistance	Passes 2000 hours QUV
Mildew Resistance	Mold & Mildew resistant
VOC	60 g/l (less water)
Pressure Classes	SMACNA 1/2, 1, 2, 3, 4, 6 and 10 inches w.g.
Seal Classes	SMACNA A, B, C
Packaging	1/12 gal. caulking cartridges, 1 gal. pails, 5 gal. pails
Freeze/Thaw Stability	Passed 5 cycles
Specifications Compliance ...	Passes ASTM C-731, ASTM C-732, ASTM D-2202, U.S.D.A. Approved

* May vary according to temperature and humidity

City of Los Angeles Approval RR#8069

- **INDOOR / OUTDOOR USE**
- **FIBER REINFORCEMENT**
- **NON-SAG FORMULATION**
- **PROVEN RELIABILITY**

APPLICATION

Apply to entire surface of duct joint

Temperature	35°F to 110°F
Method	Brush, putty knife, caulk gun, pump
Preparation	Surface must be dry, dirt, oil, and grease free.
Rate	Apply at joints and fasteners to 20 mil thick wet film
Clean Up Wet	Soap and water
Clean Up Dry	UNN-GRIP™ 798-ES or Solvent (Use safe handling practices.)
Painting	Only latex or epoxy paints

STORAGE DONOT FREEZE

Temperature	35°F to 110°F
Shelf Life	One year (unopened)
Flammability	Non-flammable

For additional information contact:

PRECAUTIONS

Surface must be clean and free of moisture, contamination and foreign matter. Do not allow this product to freeze. Do not apply when rain or freezing temperatures will occur within 36 hours.. Do not apply this product where temperatures will exceed 200°F. Keep out of the reach of children. Review MSDS for complete safety information prior to use. DO NOT use where acidic or alkaline chemicals are present (ie., lab fume hood, vents, etc.)

For Industrial Professional Use Only.



Carlisle Coatings & Waterproofing
Incorporated
900 Hensley Lane
Wylie, Texas 75098

Phone: (800) 527-7092 FAX: (972) 442-0076
WWW.HARDCAST.COM